



LEICA PINMASTER II

Technical Data



Product	LEICA PINMASTER II
Order No. Product	40 533
Delivery scope	Carrying cord, battery, Cordura case
Magnification	7 x
Front lens diameter	24 mm
Exit pupil	3.4 mm
Twilight factor	13
Field of view at 1,000 m	115 m
Field of view at 1,000 yds	347 ft
Eye-relief	15 mm
Objective angle of view	6.6°
Diopter compensation	± 3.5 diopters
Distance measurement	
Range	10 to 750 m 10 to 825 yds
Accuracy	± 1 m/yd to 366 m/400 yds, ± 2 m/yds to 750 m/825 yds, ± 0,5 % over 750 m/825 yds
Read-outs	LED display with four digits, easily legible in any light
Eyepieces for eyeglass wearers	yes
Eyecups	turn down rubber eyecups
Prism system	Roof prism with phase correction coating P40
Watertightness	Watertight to a depth of 1 m/3.2 ft
Housing	Carbon fibre-reinforced plastic material
Dimensions (W x H x D)	113 x 75 x 34 mm 4½ x 2¼ x 1¼ in
Weight	approx. 220 g / 7.8 oz incl. battery
Meter/Yard Selector	yes
Laser	Eye-safe invisible laser according to EN and FDA class 1
Laser beam divergence	approx. 0.5 x 2.5 mrad
Measuring time	maximum approx. 0.85 s
Measuring mode	Scanning mode
First target logic	The nearest distance value is displayed when several measured values are available
Power supply	1 x 3 V/Lithium-type C2R
Battery lifetime	approx. 2,000 measurements at 20°C/68°F